




Encapsulated 50Hz




Flyback transformers



Current transformers



Pulse transformers



Line coupling transformers

[▶ Encapsulated 50Hz](#)
[▶ 44000](#)
[▶ 45000](#)
[▶ 30000](#)

44000 50/60Hz PCB Mount Transformers - EI Range

Power - EI - Dimensions

3,2 VA - EI 38-13,6

Primary voltage

230



| PRIMARY VOLTAGE | | | | | | |
|-------------------------|-----------|---------------------|----------------------|-------------------|------------------------|-----------|
| Secondary protection mA | Reference | Secondary voltage V | Secondary Current mA | No-load voltage V | Ambient Temperature °C | Rating VA |
| 630 | 44193 | 6 | 533 | 8 | T 70 B | 3,2 |
| 400 | 44194 | 9 | 356 | 12 | T 70 B | 3,2 |
| 315 | 44195 | 12 | 267 | 16 | T 70 B | 3,2 |
| 250 | 44196 | 15 | 213 | 20 | T 70 B | 3,2 |
| 200 | 44197 | 18 | 178 | 24,1 | T 70 B | 3,2 |
| 160 | 44198 | 24 | 133 | 32,1 | T 70 B | 3,2 |
| 315 | 44199 | 2 x 6 | 2 x 267 | 2 x 8 | T 70 B | 3,2 |
| 200 | 44200 | 2 x 9 | 2 x 178 | 2 x 12 | T 70 B | 3,2 |
| 160 | 44201 | 2 x 12 | 2 x 133 | 2 x 16 | T 70 B | 3,2 |
| 125 | 44202 | 2 x 15 | 2 x 107 | 2 x 20 | T 70 B | 3,2 |
| 100 | 44203 | 2 x 18 | 2 x 89 | 2 x 24 | T 70 B | 3,2 |
| 80 | 44204* | 2 x 24 | 2 x 67 | 2 x 32,1 | T 70 B | 3,2 |

* to be noted : 2 x 24 V non safety transformer approved, conform to EN 61558-2-6 (Isolating transformer).

- Vacuum filling
- Two compartments bobbins
- Self-extinguishing plastics UL 94 VO
- Degree of protection IP 00
- 150 grams weight
- Resin class B CEI 85 (20 000 h testing to CEI 126)
- Fuse protection on secondary side (see table above) to be assumed by customer
- 30 V and 36 V models are VDE EN 61558-2-6 certified (production on request)
- Insulation voltage 4 KV (6 KV MYRRA test)
- 100% tested production
- Certification : CCA procedure on request

OPTIONS :

Boxes with fixing support

[View Diagram](#)

[View Picture](#)

[Go +](#)



Copyright© Myrra - Version 2011